



BV LCIE
CHINA
Number

N° 1966AS12AQRN33624

ATTESTATION of conformity with European Directives

Product: PV Microinverter (Grid-tied photovoltaic Microinverter)
Reference TSOL-M1600, TSOL-M800, TSOL-M400, TSOL-M350
Issued to TSUNESS Co., Ltd.
Address Building E1, No. 555, Chuangye Road, Dayun Town, Jiashan Country, Jiaxing City, Zhejiang Province, China
 Technical characteristics See Next Page

The submitted sample of the above equipment has been tested for **CE** marking according to following European Directive and following standards:

Low Voltage Directive 2014/35/EU

Standards	Report number	Report date
EN 62109-1: 2010 EN 62109-2: 2011	AQRN-19SE2394FTSHP-1	09/12/2019
	AQRN-19SE2394FTSHP-2	09/12/2019
	AQRN-19SE2394FTSHP-3	09/12/2019
	AQRN-19SE2394FTSHP-4	09/12/2019
	AQRN-19SE2394FTSHP-5	09/12/2019
	AQRN-19SE2394FTSHP-6	09/12/2019

The referred test report(s) show that the product complies with standard(s) recognized as giving presumption of compliance with the essential requirements in the specified European Directive

This verification does not imply assessment of the production of the product
The **CE** marking may be affixed if all relevant and effective European Directives with **CE** are applicable

Shanghai (P.R. China),), December 23th, 2019.



Harvey Wang
Product Line Manager



This document shall not be reproduced, except in full, without the written approval of BV LCIE China.
Information given in this document, are related to the tested specimen of the described electrical sample.

LCIE CHINA
必维欧亚电气技术咨询服务(上海)有限公司

Building 4, No. 518, Xin Zhuan Road,
CaoHejing Songjiang High-Tech Park,
Shanghai P.R.C (201612)

Tel: +86 21 6195 7000
Fax: +86 21 6195 7001
Email: contact@cn.bureauveritas.com



LCIE

BV LCIE
CHINA N° 1966AS12AQRN33624
Number

Model / Type.....:	TSOL-M1600	TSOL-M800	TSOL-M400	TSOL-M350
Range of Peak Power MPPT Voltage:	36-48V d.c.	33-48V d.c.	33-48V d.c.	29-48V d.c.
Max. Input voltage [V].....:	60V d.c.			
Max. Continuous Input current [A]...:	4*11,5	2*11,5	11,5	
Nominal Output voltage [V].....:	220/230/240V a.c. 50/60Hz			
Max. Continuous Output AC current [A]	7,2	3,5	1,75	1,5
Max. Continuous Output power [W] :	1500	700	350	300

Shanghai (P.R. China),), December 23th, 2019.



Harvey Wang
Product Line Manager



This document shall not be reproduced, except in full, without the written approval of BV LCIE China.
Information given in this document, are related to the tested specimen of the described electrical sample.

LCIE CHINA
必维欧亚电气技术咨询服务(上海)有限公司

Building 4, No. 518, Xin Zhuan Road,
CaoHejing Songjiang High-Tech Park,
Shanghai P.R.C (201612)

Tel: +86 21 6195 7000
Fax: +86 21 6195 7001
Email: contact@cn.bureauveritas.com