

PowerTrunk

Micro AC Coupled Unit

TSOL-MAU2000Lite/MAU4000Lite



All-in-one Unit



Charge from Grid &
Discharge to Load



Parallel Output for
Single/Three-phase Grids



Flexible Expansion



-20°C ~ +55°C Working
Temperature Range



Built-in WiFi, Bluetooth
APP Remote Monitoring



Coupled System of
Microinverter and Energy Storage



Battery Optimizer

TSUNESS Co., Ltd

sales@tsun-ess.com www.tsun-ess.com +86-512-66186028

Technical Data

Model	TSOL-MAU2000Lite	TSOL-MAU4000Lite
Battery (DC)		
Battery Type	LiFePO ₄	
Battery Capacity (kWh)	2	4
Max. System Capacity (kWh)	10	20
Nominal Voltage (V)	51.2	
Life Cycle	10,000 ^[1]	
AC Port (On-grid)		
Max. AC Output Power (W)	800 ^[2] / 2000	
Max. AC Input Power (W)	2500 ^[3]	
Nominal AC Voltage (V)	220 / 230 / 240	
Nominal AC Frequency (Hz)	50 / 60	
AC Port (Off-grid)		
Max. AC Output Power (W)	2500 ^[4]	
Nominal AC Voltage (V)	220 / 230 / 240	
Nominal AC Frequency (Hz)	50 / 60	
Switch Time (ms)	≤10	
General Data		
Dimensions (W × H × D mm)	583 × 410 × 395	
Weight (kg)	30.5	48
Communication Mode	WiFi (Bluetooth) + RS485	
Protection Degree (IP Rating)	IP65	
Cooling Method	Natural Convection	
Operating Temperature Range	-20 ~ 55°C	
Relative Humidity	0 ~ 95%, Non condensing	
Max. Operating Altitude (m)	2000	
Protection Level	I	
Overvoltage Category	II (DC); III (AC)	

[1]Designed for a lifespan of 10,000 cycles at 25 °C ambient temperature.

[2]According to the legal requirements of certain countries, such as the German region and Belgium, output load limits are implemented to 800W.

[3]The EPS load should be greater than or equal to 500W.


[4]Required AC input power greater than or equal to 500W.

Technical Data


Model	TSOL-B2000Lite	TSOL-B4000Lite
Battery Specifications		
Battery Type	LiFePO ₄	
Battery Capacity (kWh)	2	4
Nominal Voltage (V)	51.2	
Life Cycle	10,000 ^[1]	
General Data		
Dimensions (W×H×D mm)	583 × 333 × 375	
Weight (kg)	26	35
Protection Degree (IP Rating)	IP65	
Cooling Method	Natural Convection Cooling	
Operating Temperature Range	-20 ~ 55°C	
Relative Humidity	0 ~ 95%, Non condensing	
Max. Operating Altitude (m)	2000	

[1] Designed for a lifespan of 10,000 cycles at 25 °C ambient temperature.

Related Products



Diagram



MORE SAFETY MORE POWER

